

Fork Slot Truss Jibs

Fork Slot Truss Jibs - Attachments jibs can be used on industrial lift trucks, extendable-reach lift trucks, or on rough terrain straight-mast lift trucks. The forklift jib cranes could be installed onto the forklift by inserting both of the forks into the fork pockets. The rear of the jib crane then seats against the back of the fork and a safety chain wraps the forklift carriage to hold it into position.

Jib Boom Forklift Attachment Load Capacity

The most load capacity for forklift jibs in both the retracted or extended positions range beginning from 1935 lbs to as much as 6000 pounds. It is a good suggestion to ask a material handling specialist about the restrictions for your particular use. The load capacity ratings are meant for the jib itself and not the lift truck or even the utmost load that can be moved safely using a certain lift truck. It is very important remember that whenever whichever accessories like for example a forklift jib are attached to the forklift, the new center of gravity created by the attachment would lessen the general lift capability of the forklift. There are directions accessible which offer information on the way to accurately gauge these load limits.

Previous to making use of a lift truck jib, make sure that it is well secured to the lift truck with shackles and hooks. Constantly make sure in order to verify that the screw pins are tight. It is essential to also make sure that the load calculations have been made properly. Bear in mind to consider the truth that rated capacities occasionally lessen every time the boom is in a raised position, when the boom is extended with telehandlers or even each time the mast is slanted forward.